



US009638324B2

(12) **United States Patent**
Matsui et al.

(10) **Patent No.:** **US 9,638,324 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **SEALING DEVICE**

(56) **References Cited**

(71) Applicant: **NOK CORPORATION**, Tokyo (JP)

U.S. PATENT DOCUMENTS

(72) Inventors: **Hiroki Matsui**, Fukushima (JP); **Shiho Sato**, Fukushima (JP)

4,106,781 A * 8/1978 Benjamin F16J 15/3264
277/353
4,448,426 A * 5/1984 Jackowski F16J 15/3256
277/353

(73) Assignee: **NOK Corporation** (JP)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/417,923**

CN 1934379 A 3/2007
CN 102575774 A 7/2012

(Continued)

(22) PCT Filed: **Jul. 25, 2013**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/JP2013/070133**

Extended European Search Report for Patent Application No. EP 13825831.4 dated Sep. 14, 2015 (7 pages).

§ 371 (c)(1),

(2) Date: **Jan. 28, 2015**

Primary Examiner — Kristina Fulton

Assistant Examiner — Nathan Cumar

(87) PCT Pub. No.: **WO2014/021179**

PCT Pub. Date: **Feb. 6, 2014**

(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, P.L.C.

(65) **Prior Publication Data**

US 2015/0285379 A1 Oct. 8, 2015

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Jul. 30, 2012 (JP) 2012-168105

The invention provides a sealing device constructed by combination of a slinger and a lip member, the sealing device being capable of improving a sealing performance, particularly a sealing performance against external dusts. In order to achieve the object, in a sealing device having a slinger which is installed to one member among relatively rotating two members, a lip member which is installed to the other member, and structured such that the slinger integrally has a tubular portion which is fitted to the one member and a flange portion which extends in a diametrical direction, and the lip member having an end face lip which slidably comes into close contact with the flange portion, a bent portion protruding in an axial direction toward the lip member is provided in the flange portion, and a labyrinth structure having a minute gap is provided between the bent portion and the lip member.

(51) **Int. Cl.**

F16J 15/00 (2006.01)

F16J 15/3264 (2016.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16J 15/002** (2013.01); **F16J 15/3204** (2013.01); **F16J 15/3264** (2013.01); **F16J 15/447** (2013.01)

(58) **Field of Classification Search**

CPC F16J 15/002; F16J 15/3204; F16J 15/447; F16J 15/3264

(Continued)

4 Claims, 3 Drawing Sheets

